



CET35 – GRADE COLOR CODING VINYL ELECTRICAL TAPE

All weather, professional grade, pressure sensitive vinyl tape that is available in nine colors for color coding and insulating.

Cold and weather resistant. Flame retardant. Use CET35 for quick identification of electrical circuits, containers, and conduit systems, as well as primary insulation for splices at not more than 600 volts.

FEATURES AND BENEFITS

- 7 mil thickness
- Cold and weather resistant
- High dielectric strength
- Highly elastic
- Highly conformable
- High UV resistance
- Flame retardant
- Highly resistant to sun, water, oil, acids, alkalies, corrosive chemicals
- Lead free

STANDARDS

- ASTM D 3005, Type I
- ASTM D 1000
- HH-I-595C/A-A-55809A
- EN 60454-3-1, Type 11
- UL 510
- CSA C22.2 no.197

TYPICAL APPLICATIONS

- Quick identification of electrical phases, circuits, feeders and branches
- Identification of container contents, marking of piping and conduit systems and as a warning tape
- Primary insulation for splices up to 600 volts
- Wrapping wire harnesses, and insulating degaussing coils



7 mil
THICKNESS

HIGH DIALECTRIC STRENGTH

FLAME RETARDANT

MARKETS:

Industrial, Industrial OEM, Utility,
Power Distribution

STANDARDS:



Grade color coding vinyl electrical tape

DIMENSIONS

ORDER NUMBER	COLOR	THICKNESS		WIDTH		LENGTH	
		MM	IN	MM	IN	MM	IN
CET35 Red	Red	0.18	0.007	19	0.75	20	66
CET35 White	White	0.18	0.007	19	0.75	20	66
CET35 Blue	Blue	0.18	0.007	19	0.75	20	66
CET35 Yellow	Yellow	0.18	0.007	19	0.75	20	66
CET35 Orange	Orange	0.18	0.007	19	0.75	20	66
CET35 Violet	Violet	0.18	0.007	19	0.75	20	66
CET35 Brown	Brown	0.18	0.007	19	0.75	20	66
CET35 Gray	Gray	0.18	0.007	19	0.75	20	66
CET35 Green	Green	0.18	0.007	19	0.75	20	66

ORDERING

- Please specify the product name, order number and options you require
- Select options:
 - Color: Red, White, Blue, Yellow, Orange, Violet, Brown, Gray, Green
- *Example:* CET35

Please contact your Customer Service Representative for information on custom colors, sizes, lengths and material data sheet.

STORAGE

- Store the product in its original packaging in a clean dry place and placed in a horizontal position under cover in temperature conditions between 5°C to 35°C (41°F to 95°F).
- Stock rotation is recommended.

FOR FURTHER INFORMATION, PLEASE CONTACT:

Americas: 800 422 6872

Canada: 800 845 6808

Asia Pacific: +86 512 82280099

Europe: +49 2226 9047 355

All information contained in this datasheet is believed to be reliable. We advise however that customers should separately evaluate the suitability of our products for their particular application. Shawcor gives no guarantees in respect to accuracy or sufficiency of the information presented and disclaim any liability regarding its use. Our responsibilities are only those listed in our Standard Terms and Conditions of Sale for these products. In no instance will we be liable for any eventual, indirect, or consequential damage or damages arising from the sale, resale, transfer, use or misuse of the product. Subject to modification.