

CTSB-2/CTSG-1

Tape sealant

CTSB-2: Specially designed, rubber based, black sealant tape for use with heat shrink tubing CTSG-1: Cross-linked, grey butyl tape suitable for continuous high temperature applications

Features And Benefits

- Excellent adhesion to PVC, PE and steel
- Softens to fill voids
- Remains flexible over time
- Non-conductive
- Superior waterproof seal when used with other DSG-Canusa products
- Continuous operating temperature: -30°C to 85°C CTSG-1
- Protects sharp edges and smooths out transitions
- Environmentally seals areas and tubing
- Non-conductive
- Excellent high temperature performance
- Resistant to common fluids and solvents
- High dielectric strength (310 V/mil)
- Continuous operating temperature: -30°C to 105°C

Typical Applications

- Insulating and sealing electrical connections
- Padding over irregular surfaces

Ordering

- Select the appropriate tape sealant.
- Please specify the product name plus the options you require
- Order Example: CTSG-1

Please contact your Customer Service Representative for information on tape sealant and material data sheet.



ORDER NUMBER

WIDTH

THICKNESS

ROLL LENGTH

	MM	IN	MM	IN	MM	IN
CTSB-2 (Black)	50.8	2.0	15	0.06	7620	300
CTSG-1 (Grey)	25.4	1.0	15	0.06	7620	300

Version: 01 2018/JAN/02