

Legrand cabling system LCS³ cat. 8

flat equipped patch panel

New LCS³ system

Automatic cassette extraction



0 337 82

| Pack | Cat.Nos | Cat. 8 patch panel equipped with 24 RJ 45 connectors |
|------|----------|--|
| 1 | 0 337 82 | <p>Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures</p> <p>Universal mounting on any cabinet or enclosure</p> <p>The panel ensures automatic earthing of each connector</p> <p>Equipped with rear cable guide to hold the cables during maintenance</p> <p>Equipped with 4 cassettes of 6 cat. 8 RJ 45 LCS³ quick-connect connectors (no tools required), with 568 A/B marking</p> <p>Supplied with coloured labels</p> <p>Compliant with ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 standards</p> <p>19" patch panel - 1 U</p> <p>Automatic cassette removal by simple pressure</p> <p>Possibility of individual extraction of each connector</p> <p>Flat panel</p> <p>STP panel - Metal shielding</p> |

Legrand cabling system LCS³ cat. 8

flat patch panels to be equipped



0 337 90

| Pack | Cat.Nos | Flat 24-connector patch panels - 1 U to be equipped |
|------|----------|---|
| 1 | 0 337 90 | <p>Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures</p> <p>Universal mounting on any cabinet or enclosure.</p> <p>The panels ensure automatic earthing of each connector.</p> <p>Equipped with rear cable guide to hold the cables during maintenance</p> <p>Flat panel with empty cassettes to be equipped with connectors</p> <p>Equipped with 4 automatic extraction cassette for cat. 5e to cat. 8 RJ 45 connectors</p> <p>19" patch panel - 1 U</p> <p>Empty flat panel to be equipped with cassette</p> <p>It can accept a maximum of 4 automatic extraction cassettes:</p> <ul style="list-style-type: none"> - copper - fibre optic |
| 1 | 0 337 91 | <p>19" patch panel - 1 U</p> |

Legrand cabling system LCS³ cat. 8

angled patch panel to be equipped with connectors



0 337 92



0 337 85

| Pack | Cat.Nos | |
|------|----------|---|
| 1 | 0 337 92 | <p>Angled 24-connector patch panel - 1 U</p> <p>Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures Universal mounting on any cabinet or enclosure The panel ensures automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance</p> <p>Angled panel to be equipped with connectors It can accept up to 24 cat. 5e to cat. 8 RJ 45 connectors 19" panel - 1 U</p> |
| 1 | 0 337 85 | <p>Cat. 8 RJ 45 connectors for flat and angled STP panel</p> <p>Quick-connect connection (no tools required), with 568 A/B marking Supplied with coloured labels Compliant with the following standards ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 Set of 6 RJ 45 connectors For installation in the cassettes of flat or angled panels</p> |

Legrand cabling system LCS³ cat. 8

equipment and accessories



0 337 56



0 337 59



0 337 55



0 337 57



0 337 58

| Pack | Cat.Nos | |
|------|----------|--|
| 10 | 0 337 56 | <p>Common accessories for flat and angled panels</p> <p>Port blanking modules Divisible 6 port blanking plate for sealing from 1 to 6 ports</p> |
| 1 | 0 337 59 | <p>Cord management 2 cord management for use with new generation Quick-Fix They provide side cord management</p> |
| 1 | 0 337 55 | <p>Specific accessories for flat panels</p> <p>Cassette for flat panels to be equipped Empty removable cassette to be equipped with connectors. It can accept 6 cat. 5e to cat. 8 connectors. Extraction by simple pressure of the cassette making installation and maintenance easier</p> |
| 1 | 0 337 57 | <p>Blanking cassette Used to blank the panel</p> |
| 1 | 0 337 58 | <p>Specific accessories for angled panels</p> <p>Angled panel cover For optimised management of the air flow inside the cabinet</p> |

Legrand cabling system LCS³ cat. 8

cables and cords



0 337 88



0 337 03



0 518 90

| Pack | Cat.Nos | |
|------------------|----------|--|
| | | Cat. 8 local network cables |
| | | 4 twisted pair cables, 100 Ω LSOH sheath: without halogens EIA/TIA colour code Compliant with ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 standards |
| 500 ¹ | 0 337 86 | F/UTP - 4 pairs Performance 2000 MHz Length 500 m supplied on drum. Weight 42 kg |
| 500 ¹ | 0 337 88 | S/FTP - 4 pairs Performance 2000 MHz Length 500 m supplied on drum. Weight 45 kg |
| | | Cat. 8 RJ 45 patch cords |
| | | RJ 45/RJ 45 flat With special "easy grip" plug Compliant with ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 standards |
| | | S/FTP shielded, impedance 100 Ω |
| | | Length 0.5 m |
| | | Length 1 m |
| | | Length 2 m |
| | | Length 3 m |
| | | Length 5 m |
| | | Length 8 m |
| | | Length 10 m |
| | | LSZH |
| | | |
| | | RAL 6027 |
| | | 0 337 01 |
| | | 0 337 02 |
| | | 0 337 03 |
| | | 0 337 04 |
| | | 0 337 05 |
| | | 0 337 06 |
| | | 0 337 07 |
| | | LSZH |
| | | |
| | | RAL 3020 |
| | | 0 337 21 |
| | | RAL 6026 |
| | | 0 337 08 |
| 1 | | 0 337 22 |
| | | 0 337 09 |
| | | 0 337 23 |
| | | 0 337 10 |
| | | 0 337 24 |
| | | 0 337 11 |
| | | 0 337 25 |
| | | 0 337 12 |
| | | 0 337 26 |
| | | 0 337 13 |
| 1 | | 0 337 27 |
| | | 0 337 17 |
| | | Length 0.5 m |
| | | Length 1 m |
| | | Length 2 m |
| | | Length 3 m |
| | | Length 5 m |
| | | Length 8 m |
| | | Length 10 m |
| | | Marking kit |
| 1 | 0 518 90 | Kit of 200 coloured rings for marking RJ 45 cords Rings to be clipped to the patch cords 1: in metre(s) |

Legrand cabling system LCS³ cat. 6_A

flat equipped patch panels

Automatic cassette extraction




0 337 72

| Pack | Cat.Nos | |
|------|----------|---|
| | | Cat. 6_A patch panels equipped with 24 RJ 45 connectors |
| | | Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures Universal mounting on any cabinet or enclosure The panels ensure automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance Equipped with 4 cassettes of 6 cat. 6 _A RJ 45 LCS ³ quick-connect connectors (no tools required), with 568 A/B marking Supplied with coloured labels Compliant with ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 standards |
| | | 19" panel - 1 U Automatic cassette removal by simple pressure |
| | | Flat panels |
| | | 24 RJ 45 connectors - 1 U |
| 1 | 0 337 70 | UTP |
| 1 | 0 337 72 | STP |

Legrand cabling system LCS³ cat. 6_A

flat patch panels to be equipped



0 337 90



0 337 93

| Pack | Cat.Nos | |
|------|----------|--|
| | | Flat 24-connector patch panels - 1 U to be equipped |
| | | Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures Universal mounting on any cabinet or enclosure The panels ensure automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance |
| | | Flat panel with empty cassettes to be equipped with connectors |
| | | Equipped with 4 automatic extraction cassettes for cat. 5e to cat. 8 RJ 45 connectors |
| 1 | 0 337 90 | 19" panel - 1 U |
| | | Empty flat panel to be equipped with cassettes |
| | | It can accept a maximum of 4 automatic extraction cassettes: |
| | | - copper |
| | | - fibre optic |
| 1 | 0 337 91 | 19" panel - 1 U |
| | | Flat high density 48-connector patch panel - 1 U to be equipped |
| | | Universal mounting on any cabinet or enclosure The panel ensures automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance Automatic cassette removal by simple pressure Possibility of removing each connector individually |
| 1 | 0 337 93 | 19" panel - 1 U |

Legrand cabling system LCS³ cat. 6_A

angled patch panels to be equipped with connectors



0 337 92



0 337 94



0 337 75

| Pack | Cat.Nos | |
|------|----------|---|
| | | Angled 24-connector patch panel - 1 U |
| | | Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures Universal mounting on any cabinet or enclosure The panel ensures automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance |
| | | Angled panel to be equipped with connectors |
| | | It can accept up to 24 cat. 5e to cat. 8 RJ 45 connectors |
| 1 | 0 337 92 | 19" panel - 1 U |
| | | Angled high density 48-connector patch panel - 1 U to be equipped |
| | | Complete with new generation Quick-Fix for automatic mounting (no screws required) on the risers of cabinets or enclosures Universal mounting on any cabinet or enclosure The panel ensures automatic earthing of each connector Equipped with rear cable guide to hold the cables during maintenance |
| | | Angled panel to be equipped with connectors |
| | | It can accept up to 48 cat. 5e to cat. 6 _A RJ 45 connectors |
| 1 | 0 337 94 | 19" panel - 1 U |
| | | High density cat. 6_A RJ 45 connectors |
| | | Cat. 6A RJ 45 connectors for flat and angled STP panels Quick-connect connection (no tools required), with 568 A/B marking Supplied with coloured labels Compliant with ISO/IEC 11801 edition 3.0 (2017) and EIA/TIA 568 C2-1 standards For equipment to be installed in the cassettes of flat or angled panels |
| | | Set of 6 cat. 6 _A RJ 45 connectors |
| 1 | 0 337 73 | UTP |
| 1 | 0 337 75 | STP |




| Pack | Cat.Nos | Common accessories for flat and angled panels |
|------|----------|--|
| 10 | 0 337 56 | Port blanking modules Divisible 6 port blanking plate For sealing from 1 to 6 ports |
| 1 | 0 337 59 | Cord management For use with new generation Quick-Fix; they provide side cord management |

| Pack | Cat.Nos | Specific accessories for flat panels |
|------|----------|--|
| 1 | 0 337 55 | Cassette for flat panels to be equipped Empty removable cassette to be equipped with connectors. It can accept 6 cat. 5e to cat. 8 connectors Extraction by simple pressure of the cassette making installation and maintenance easier Possibility of removing each connector individually |
| 1 | 0 337 95 | High density cassette for flat panels to be equipped Empty removable cassette to be equipped with connectors; it can accept 12 cat. 5e to cat. 6 _A connectors Extraction by simple pressure of the cassette, making installation and maintenance easier |
| 1 | 0 337 57 | Blanking cassette Used to blank the panel |

| Pack | Cat.Nos | Specific accessories for angled panels |
|------|----------|--|
| 1 | 0 337 58 | Angled panel cover For optimised management of the air flow inside the cabinet |

Legrand cabling system LCS³ cat. 6_A

cables and cords



| Pack | Cat.Nos | Cables for local networks cat. 6A |
|------------------|----------|---|
| 500 ¹ | 0 327 87 | <p>LSZH</p> <p>U/UTP - 4 pairs Performance 500 MHz Length 500 m Supplied on reel. Weight 25 kg</p> |
| 500 ¹ | 0 327 78 | <p>F/UTP - 4 pairs Performance 500 MHz Length 500 m Supplied on reel. Weight 25 kg</p> |
| 500 ¹ | 0 328 78 | <p>F/UTP - 2 x 4 pairs Performance 500 MHz Length 500 m Supplied on reel. Weight 65 kg</p> |
| 500 ¹ | 0 327 77 | <p>S/FTP - 4 pairs Performance 600 MHz Length 500 m Supplied on reel. Weight 30 kg</p> |

1: in metre(s)

| Pack | Cat.Nos | RJ 45 patch cords and user cords cat. 6A |
|------|----------|--|
| 1 | 0 518 82 | <p>PVC</p> <p>RJ 45 - RJ 45 right Conform to standards ISO/IEC 11801 Ed. 2.0, EN 50173-1 and TIA/EIA 568C U/UTP unshielded impedance 100 Ω Length 1 m</p> |
| 1 | 0 518 83 | Length 2 m |
| 1 | 0 518 84 | Length 3 m |
| 1 | 0 518 85 | Length 5 m |
| 1 | 0 518 78 | <p>LSZH</p> <p>Length 1 m</p> |
| 1 | 0 518 79 | Length 2 m |
| 1 | 0 518 80 | Length 3 m |
| 1 | 0 518 81 | Length 5 m |
| 1 | 0 518 74 | Length 1 m |
| 1 | 0 518 75 | Length 2 m |
| 1 | 0 518 76 | Length 3 m |
| 1 | 0 518 77 | Length 5 m |
| 1 | 0 518 16 | <p>PVC</p> <p>S/FTP shielded impedance 100 Ω Length 0.5 m</p> |
| 5 | 0 517 80 | Length 1 m |
| 5 | 0 517 81 | Length 2 m |
| 5 | 0 517 82 | Length 3 m |
| 5 | 0 517 83 | Length 5 m |
| 1 | 0 518 70 | <p>LSZH</p> <p>Length 1 m</p> |
| 1 | 0 518 71 | Length 2 m |
| 1 | 0 518 72 | Length 3 m |
| 1 | 0 518 73 | Length 5 m |
| 1 | 0 518 66 | Length 1 m |
| 1 | 0 518 67 | Length 2 m |
| 1 | 0 518 68 | Length 3 m |
| 1 | 0 518 69 | Length 5 m |

Legrand cabling system LCS³ cat. 6A

RJ 45 sockets - Mosaic™ Programme



Can be integrated in all supports (see Legrand general catalog)
 Mechanisms to be equipped with support frames (see Legrand general catalog) and plates (see Legrand general catalog)
 With LCS³ connector with fast connection thanks to integrated crimping take AWG 22 single-core cables up to AWG 26 and AWG multicore cables
 Contacts marked with dual colour code and wiring schemes T568 A and T 568 B
 Conform to standards ISO/IEC 11801 Ed. 2.0, amendment 2, EN 50173-1 and TIA/EIA 568 C

| Pack | Cat.Nos | Mosaic Programme RJ 45 sockets cat. 6A | Pack | Cat.Nos | Keystone RJ 45 sockets cat. 6A |
|------|----------|---|------|----------|--|
| 10 | 0 765 73 | STP - 1 module 360° metal shielding ○ White | 10 | 0 331 54 | STP socket - metal shielding 360° with fast connection thanks to integrated crimping |
| 10 | 0 765 84 | ○ White antimicrobial | 10 | 0 331 55 | UTP socket - with fast connection thanks to integrated crimping |
| 10 | 0 794 73 | ● Aluminium | | | |
| 10 | 0 765 76 | STP - 2 modules 360° metal shielding ○ White | | | |
| 10 | 0 794 76 | ● Aluminium | | | |
| 10 | 0 765 24 | ○ White with green blank | | | |
| 10 | 0 765 25 | ○ White with orange blank | | | |
| 10 | 0 765 08 | ○ White | | | |
| 5 | 0 765 99 | STP with controlled access - 2 modules 360° metal shielding Supplied with 2 keys for 5 sockets ○ White with red blank | | | |
| 10 | 0 765 71 | UTP - 1 module ○ White | | | |
| 10 | 0 794 71 | ● Aluminium | | | |
| 10 | 0 765 26 | ○ White with green blank | | | |
| 10 | 0 765 27 | ○ White with orange blank | | | |
| 10 | 0 765 74 | UTP - 2 modules ○ White | | | |
| 10 | 0 794 74 | ● Aluminium | | | |
| 5 | 0 765 90 | UTP with controlled access - 2 modules Supplied with 2 keys for 5 sockets ○ White with red blank | | | |
| 10 | 0 765 09 | ○ White | | | |
| | | | | | Surface-mounting 1 or 2 ports box For keystone connectors Provides a solution for the integration of a keystone in surface-mounting installations Can be fixed on table or in association with mini-trunking |