

CRDW-CT

1 kV cable tap splice kit

Adhesive lined, heat shrink wraparound sleeve that is closed with a flexible stainless-steel locking channel. Used for making in-line Y or H parallel splices on cable up to 1000 V without cutting the main or run cable.

Features And Benefits

- Provides water tight seal upon recovery
- Offers mechanical durability
- Suitable for connecting Main and Tap runs to 500 kcmil size
- Accommodates compression and split bolt connectors
- High shrink ratio covers irregular shapes
- High impact and abrasion resistance
- Application procedure is quick, simple and clean
- Steel channel provides permanent closure system
- Installation temperature range: -15°C to 50°C

Typical Applications

- Cable tap splicing
- General re-jacketing and sealing of electrical cables

Note

- Split bolts can only be used up to #2 AWG Main and Branch cable sizes

Ordering

- Select the cable run and tap combination and confirm that the connector dimensions are not exceeded.
- Please specify the product name plus the options you require
- Order Example: CRDW-CT1

Please contact your Customer Service Representative for information on non-standard sizes, combinations and material data sheet.



| ORDER NUMBER | MAIN (RUN) CABLE SIZE | BRANCH (TAP) CABLE SIZE | CONNECTOR DIMENSIONS | SLEEVE LENGTH |
|--------------|-----------------------|-------------------------|----------------------|---------------|
| | AWG/Kcmil | AWG/Kcmil | (Max) D | IN |

| ORDER NUMBER | MAIN (RUN) CABLE SIZE | BRANCH (TAP) CABLE SIZE | CONNECTOR DIMENSIONS | SLEEVE LENGTH |
|--------------|-----------------------|-------------------------|----------------------|---------------|
| CRDW-CT1 | #8 - #2 | #10 - #2 | 2 | 6 |
| CRDW-CT2 | #2 - 4/0 | #10 - 4/0 | 4 | 8 |
| CRDW-CT3 | 4/0 - 500 | #2 - 500 | 6 | 10 |

Version: 01 2018/JAN/02