

SpecSeal®

AS200

WATER-BASED ELASTOMERIC FIRESTOP SPRAY

# Elastomeric Spray

SpecSeal® AS200 Elastomeric Spray is a latex-based elastomeric firestop spray for construction joints and perimeter fire barrier applications. AS200 cures to form a durable seal that resists the passage of flames, hot gases, and smoke while allowing for dynamic joint movement.

## Features & Benefits

- Applied with airless spray equipment
- Highly flexible to accommodate for dynamic joint conditions
- Tested for up to 4 Hour fire resistance rating when tested to ASTM E1966/UL 2079
- Listed in over 100 UL® Tested curtain wall and joint systems



## ORDERING INFORMATION

Catalog Number	UPC Number	Size	(UOM) Qty.	Case Qty.	Weight (Each)
AS205	730573071076	5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	53.60 lbs (24.31 kg)
AS205R	730573071083	5 Gallon Pail - 1,155 cu. in. (19 liters)	1	1	53.60 lbs (24.31 kg)

**TEST STANDARDS:** ASTM E814 (UL 1479), ASTM E1966 (UL 2079), ASTM E2307, CAN/ULC S115, ASTM E84 (UL 723), ASTM E90

 Pale Blue Color  
 Red Color

 Permanent Solution

**ACOUSTICAL**  
STC 60 (Relates to specific construction)

**MOVEMENT**  
+50% Maximum Movement Capability

 UL CERTIFIED

 FM APPROVED

 FBC SYSTEM COMPATIBLE

 Intertek



1-800-992-1180  
stifirestop.com



Click here to learn more about



ZSTI3536 3299